

P-8610 Load Share & Paralleling



- Black ABS UV Protected Corrosion Proof Cabinet with Corrosion Resistant Hardware (15.5" W X 11.25" H X 10.75" D)
- Deep Sea **DSE8610** Auto Start Load Sharing & Synchronizing Module
- Front panel configurable with external panel mounted USB port
- Panel mounted and programmed pilot relays for; start, run and auxiliary output
- Supplied 85 amp start solenoid shipped loose
- Color coded engine harness with cannon plug
- Color coded AC harness exits the bottom of the panel
- Color coded paralleling interconnection harness
- Panel vibration mounts, 6 foot USB programming cable & electrical schematics included
- Includes a VDO 1/8" NPT Oil Pressure and 3/8" NPT Coolant Sender
- Current Transformers are sold separately

FOR A QUOTE OR TO ORDER

Please contact us with the; kW, ac & dc voltage, phase & frequency
Panels are programmed with the supplied application data

PANEL OPTIONS

- DS16** 12Vdc Aux. Relay 40A
- DS17** 24Vdc Aux. Relay 30A
- DS32** SPDT Toggle Switch
- DS40** Alarm Buzzer (90db)
- DS45B** AC Output Harness
- DS45C** Common Bus Harness
- DS67** Emergency Stop Button
- DS20** 12Vdc 3PDT 10A Plug-in
Form C Relay
- DS21** 24Vdc 3PDT 10A Plug-in
Form C Relay
- DS74** Qty. 1 DS2157-01
Modules

OPTIONAL MODULES

- DSE2157-01** Output Expansion
Module 8 configurable (NO or
NC) contacts rated at 2 Amp DC
- DSE2130-00** Input Expansion
Module 8 inputs .75 Mile Range
- DSE890MKII** 4G Ethernet Web
Gateway Requires 4G LTE
Service & GPS Antenna
- P6-16-DS** 16 LED Remote Annun-
ciator with horn Wall or Flush
Mount 8" X 10" Enclosure