

Custom Remote Annunciator

STANDARD FEATURES



ENGINE & GENERATOR CONTROLS

P6-08-DS & P6-16-DS

Panelsource annunciator panel for use with Deep Sea 73X0, 74X0, 86X0, and 87X0 controllers.

Built around the Deep Sea 2548 LED Expansion Module with 8 red LEDs, audible horn, and text card insert.

16 LED version - modules are pre-wired together with power and data connection between modules, including wired 120 ohm termination resistor

Module requires 12-24VDC nominal power and Belden 9841 or equivalent 120 ohm twisted pair communication cable. Up to 1000M distance from host controller using Belden 9841. Davidson Sales stocks Belden 9841. Inquire with sales.

Enclosure: Type 1, Enamel coated steel. Faceplate: ABS UV resistant faceplate.

P6-8-DS Flush



P6-16-DS Wall

NFPA 110 Level 1 pre-programming available on P6-16-DS

LED indication conditions field programmable through host controller using a PC and Deep Sea Configuration Suite Software.

Dimensions 8.00" (w) x 10.00" (h) x 4.25" (d) **P6-08-DS (Wall Mount)**

Dimension 9.50" (w) x 11.50" (h) x 4.25" (d) **P6-08-DS (Flush Mount)**

Dimensions 9.50" (w) x 10.00" (h) x 4.25" (d) **P6-16-DS (Wall Mount)**

Dimensions 13.50" (w) x 11.50" (h) x 4.25" (d) **P6-16-DS (Flush Mount)**

Dimensions

National Marketing and Distribution by Davidson Sales Co.

839 Bill France Blvd., Daytona Beach, FL 32117

Phone: (386)274-2079 Fax: (386)274-2279 www.davidsonsales.com